



CC2012 CLEARCOTE

CLEAR ACRYLIC TOPCOAT FOR DECORATIVE RACK PLATING

USES

- Clear, acrylic topcoat for decorative rack plating.
- Used for gold, silver, sterling, copper and copper alloys.

FEATURES

- Water-based, clear acrylic.
- Eliminates silver tarnish.
- 90% reduction of VOCs.
- Uniform coverage.
- Improves wear, reduces gold thickness.

APPLICATION METHODS

- It can be apply by dipping, spraying.
- The parts to be Dip-coated must be pre-heated above 60°C, before dipping.

TECHNICAL DATA

- | | |
|--|--------------------|
| • Appearance: | Translucent liquid |
| • Emulsifier Charge: | Amine dispersed |
| • Solids Type: | Acrylic Copolymer |
| • Curing Temperature: | 60 °C |
| • Non-Volatile (%): | 24.0 - 26.0 |
| • Brookfield Viscosity (cps): | < 500 |
| • Spindle Number: | 2 |
| • RPM: | 60 |
| • pH: | 7.5 - 9.5 |
| • ASTM hardness | 50. |
| • Melting point | 79°C |
| • Recommended pH of your system: | > 7 |
| • Specific Gravity (g/cm ³): | 0.98 - 1.00 |

PACKING

5 kg - plastic-pail / 20 kg - plastic pail

Disclaimer:

The information provided in this brochure is ensured to be as accurate as possible at the time of inclusion, however there may be inadvertent and occasional errors which may have slipped from our notice. Warrior Pte Ltd does not guarantee and make no representations or warranties of any kind about the information, advice and opinions provided and reserves the right to make changes and corrections at any time, without prior notice to any parties. Warrior Pte. Ltd. accepts no liability for any inaccuracies or omissions in its brochure and any decisions made based on information and opinions contained in the brochure is the sole responsibility of the user.

WARRIOR PTE LTD

Blk 17 Marsiling Industrial Estate Road 1 # 01-11 Singapore 739279

Tel: (65) 6364 5100 / 6364 5060 / 6367 3676 Fax: (65) 6364 0629

war99@singnet.com.sg www.warrior.com.sg

