













WARRIOR PTE LTD

Block 17 Marsiling Industrial Estate Road 1,
#01-11 Singapore 739279
war99@singnet.com.sg www.warrior.com.sg

Shelf Life: 5 Years
Tel: 6364 5100
Fax: 6364 0629
Brand [JiChuan](#)

Main Ingredients: Detergent, decomposer, special anti-slip solution, etc.

Resturant Kitchen Ceramic Tile Flooring Anti-Slip Solution

Product Image						
Location Material						
Volume Specifications	350g x 2 bottles (set : includes tools)	20 sets/box	350g (bottle)	350g (30 bottles/box)	5kg (bottle)	10kg (bottle)
Coverage	16 m ²	320 m ²	8 m ²	240 m ²	120 m ²	240 m ²
Product Summary	<p>1. This solution is suitable for kitchens in restaurants, eateries, schools and similar establishments. Do not use in residential kitchens.</p> <p>2. This solution will not work with homogenous tiles. If no anti-slip effect is produced after application, then the tile is a homogenous tile, in which case kindly switch to the "Homogenous Tile Anti-Slip Solution". Homogenous Tiles are tiles that possess uniform colouring throughout the tile, inside out, because the dye is mixed into the tile itself as opposed to having been glazed onto the surface like normal tiles. A close look at the surface of a homogenous tile will reveal a myriad of tiny dots, with colours other than that of the tile's overall colour, spread all over the tile.</p> <p>3. This solution will form countless anti-slip holes on the tile surface, each just microns in size, creating an excellent anti-slip effect. Long lasting anti-slip performance is secured because these anti-slip holes are permanent and do not dissipate. The solution itself is a clear, water-based liquid, and will not leave residues or change tile appearance after application. Application is fast, easy, and achieves cleaning, disinfection and anti-slippage in one easy step.</p>					
Application Instruction	<p>1. There is no need to clean the tile surface prior to application; simply apply the solution to dry tiles. For small area applications using hand brush, lightly squeeze some solution into a plastic bowl and dip the brush into it such that the solution covers the brush, then lean the brush to drip any excess solution back into the bowl (until the dripping slows to a drop). Spread the solution from left to right, move down, then spread the solution from right to left, alternating as such until the area is covered. Then, going back to the starting point, spread the solution all the way down, move right, spread the solution all the way up, and so on (the criss cross method). Every dip into the solution should cover about 60cm x 60cm. For large area applications using microfiber mop, pour the solution into a waxing bucket, place the mop into the bucket, let the solution soak in, then squeeze the excess solution back into the bucket with the bucket's wringer--simply press down for about 5 seconds, using moderate pressure, lift, then repeat (until the solution does not drip upon lifting). To apply, start from the top and mop downwards; then, moving the mop a bit to the side, mop upwards. Now flip the microfiber mop and mop back, tracing the original path, to the starting position. Every dip into the bucket should cover about 150cm x 150cm. When the desired area is mopped completely, leave it for 10 minutes, then clear the remaining solution by flushing with large amounts of water, or by mopping with water. Then the task is done. If the solution was not thoroughly washed off after application, it will form a white powder once dry. Therefore, when mopping the floor, to change the water frequently and thoroughly remove the solution. Please wash the equipment with water before storing.</p> <p>2. Certain floor surfaces lose a bit of gloss after application, but when used on suitable material, there is basically little change in gloss. If the gloss is excessively decreased then the anti-slip function may be excessively strong, such that dirt accumulates easily and cleaning becomes difficult. Test the solution on an inconspicuous spot prior to general application; if there is excessive loss in gloss, do not use this product.</p> <p>3. Slipping is caused by people losing balance on overly smooth surfaces, falling as a result. The anti-slip solution, when applied correctly, can prevent slipping by creating an appropriate level of friction and vacuum suction, all the while retaining gloss. Please use according to instructions: apply only a thin layer of solution, not too much, and apply once only. A second application is necessary only when the anti-slip functionality is clearly insufficient.</p>					
Items of Note	<p>1. There are no particular restrictions in terms of cleaning a treated floor--simply keep it free of dirt and oil. An oil-free surface needs no particular cleaning. If anti-slippage dissipates due to oil plugging the anti-slip holes, please remove the oil by brushing with a cleaning solution, or simply apply "Ceramic Tile #2 Anti-Slip Solution", a weaker anti-slip product, to regain the original non-slip effect. Do not vitrify, wax, or apply cleaning/glossing solutions containing wax to a treated floor. Wax will plug the micro anti-slip holes and remove their anti-slipping effect.</p> <p>2. Do not mix the anti-slip solution with bleach, cleaning solutions or other chemical solutions. This solution has a slight odour but is not pungent, so if a pungent odour is detected during application, stop the treatment process, rinse off any bleach or cleaning product residues using water, and then resume application.</p> <p>3. During application, please wear shoes and plastic gloves, and maintain ventilation. If the solution makes skin contact, please wash with soap. If the solution gets into the eye, flush the eye for 15 minutes with plenty of water and seek medical attention immediately. If the solution is mistakenly swallowed, drink lots of milk and seek medical attention immediately. This solution may cause colour change when applied to metal, glass fiber, plastic, clothing, shoes, or other non-suitable material, so please avoid such contact. If such contact is made, rinse with water immediately. For storage, use the original container and do not switch to other containers. Make sure the cap is closed tightly, and store in a dark or shaded location, away from children.</p>					